



SOAP-over-UDP Version 1.1

Committee Draft 02

27 January 2009

Specification URIs:

This Version:

<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-02/wsdd-soapoverudp-1.1-spec-cd-02.html>
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-02/wsdd-soapoverudp-1.1-spec-cd-02.docx>
(Authoritative Format)
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-02/wsdd-soapoverudp-1.1-spec-cd-02.pdf>

Previous Version:

<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-01/wsdd-soapoverudp-1.1-spec-cd-01.html>
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-01/wsdd-soapoverudp-1.1-spec-cd-01.docx>
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/cd-01/wsdd-soapoverudp-1.1-spec-cd-01.pdf>

Latest Version:

<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/wsdd-soapoverudp-1.1-spec.html>
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/wsdd-soapoverudp-1.1-spec.docx>
<http://docs.oasis-open.org/ws-dd/soapoverudp/1.1/wsdd-soapoverudp-1.1-spec.pdf>

Technical Committee:

OASIS Web Services Discovery and Web Services Devices Profile (WS-DD) TC

Chair(s):

Toby Nixon, Microsoft Corporation
Alain Regnier, Ricoh Company Limited

Editor(s):

Ram Jeyaraman, Microsoft Corporation

Declared XML Namespace(s):

None.

Abstract:

This specification defines a binding for SOAP envelopes to use datagrams.

Status:

This document was last revised or approved by the WS-DD TC on the above date. The level of approval is also listed above. Check the "Latest Version" or "Latest Approved Version" location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/ws-dd/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/ws-dd/ipr.php>).

The non-normative errata page for this specification is located at <http://www.oasis-open.org/committees/ws-dd/>.

Notices

Copyright © OASIS® 2009. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is trademarks of OASIS, the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <http://www.oasis-open.org/who/trademark.php> for above guidance.

Table of Contents

1	Introduction.....	4
1.1	Requirements	4
1.2	Notational Conventions.....	4
1.3	Terminology	5
1.4	XML Namespaces	5
1.5	Relationship to Web Service Specifications	5
1.6	Normative References	5
2	UDP Packet.....	7
2.1	Source Address and Port.....	7
2.2	Data Octets	7
3	Message Patterns.....	8
3.1	One-way.....	8
3.1.1	One-way Example	8
3.2	Request-response	8
3.2.1	Anonymous [reply endpoint].....	8
3.2.2	Request Example 1	9
3.2.3	Response Example 1	9
3.2.4	Request Example 2	10
3.2.5	Response Example 2	10
3.3	Multicast.....	11
3.4	Retransmission	11
4	Message Encoding	12
5	URI Scheme	13
5.1	Syntax	13
5.2	Semantics	13
6	Security Considerations	14
7	Conformance	15
A.	Appendix (non-normative) — Example retransmission algorithm	16
B.	Appendix (non-normative) — Example duplicate detection mechanisms.....	17
C.	Acknowledgements	18
D.	Revision History.....	20

1 Introduction

Many application protocol patterns match the semantics of the User Datagram Protocol (UDP) [RFC 768]

Some do not require the delivery guarantees of TCP while others make use of multicast transmission. In order to allow Web services to support these patterns, we need a way to map SOAP envelopes to user datagrams. This support is essential for services using WS-Discovery, where the use of multicast and need for low connection overhead makes UDP a natural choice. It is anticipated that other protocols will have similar requirements. This specification defines a binding of SOAP to user datagrams, including message patterns, addressing requirements, and security considerations.

1.1 Requirements

This specification intends to meet the following requirements:

- Support a one-way message-exchange pattern (MEP) where a SOAP envelope is carried in a user datagram.
- Support a request-response message-exchange pattern (MEP) where SOAP envelopes are carried in user datagrams.
- Support multicast transmission of SOAP envelopes carried in user datagrams.

Support both SOAP 1.1 [SOAP 1.1] and SOAP 1.2 [SOAP 1.2 Part 1]

Envelopes.

1.2 Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119]

This specification uses the following syntax to define normative outlines for messages:

The syntax appears as an XML instance, but values in italics indicate data types instead of literal values.

Characters are appended to elements and attributes to indicate cardinality:

- "?" (0 or 1)
- "*" (0 or more)
- "+" (1 or more)
- The character "|" is used to indicate a choice between alternatives.
- The characters "[" and "]" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.
- Ellipses (i.e., "...") indicate points of extensibility. Additional children and/or attributes MAY be added at the indicated extension points but MUST NOT contradict the semantics of the parent and/or owner, respectively. If a receiver does not recognize an extension, the receiver SHOULD ignore the extension.
- XML namespace prefixes (see Table 1) are used to indicate the namespace of the element being defined.

Elsewhere in this specification, the characters "[" and "]" are used to call out references and property names. This specification uses the **[action]** and Fault properties **[WS-Addressing]**

to define faults.

41 1.3 Terminology

42 Receiver

43 The endpoint terminating a SOAP/UDP datagram

44 Sender

45 The endpoint originating a SOAP/UDP datagram

46 SOAP/UDP datagram

47 A user datagram containing a SOAP envelope in the data octets

48 User datagram

49 A User Datagram Protocol (UDP) packet

50 1.4 XML Namespaces

51 The following lists XML namespaces that are used in this specification. The choice of any namespace
52 prefix is arbitrary and not semantically significant.

53 **Table 1: Prefix and XML Namespaces used in this specification.**

Prefix	XML Namespace	Specification(s)
S	(Either SOAP 1.1 or 1.2)	(Either SOAP 1.1 or 1.2)
s11	http://schemas.xmlsoap.org/soap/envelope/	[SOAP 1.1]
s12	http://www.w3.org/2003/05/soap-envelope	[SOAP 1.2 Part 1]
A	http://www.w3.org/2005/08/addressing	[WS-Addressing]

54 1.5 Relationship to Web Service Specifications

55 This specification provides a binding appropriate for:

- 56 • SOAP 1.1 [SOAP 1.1]

57 SOAP 1.2 [SOAP 1.2 Part 1]

58 Messages conforming to either SOAP specification can use this binding. This specification relies on WS-
59 Addressing [WS-Addressing]

60 .

61 1.6 Normative References

62 [RFC 768]

63 J. Postel, "User Datagram Protocol," RFC 768, <http://www.ietf.org/rfc/rfc768.txt>, August 1980.

64 [RFC 2119]

65 S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119,
66 <http://www.ietf.org/rfc/rfc2119.txt>, March 1997.

67 [RFC 2365]

68 D. Meyer, "Administratively Scoped IP Multicast," RFC 2365, <http://www.ietf.org/rfc/rfc2365.txt>,
69 July 1998.

70 [RFC 3986]

71 T. Berners-Lee, et al, "Uniform Resource Identifiers (URI): Generic Syntax", IETF RFC 3986,
72 <http://www.ietf.org/rfc/rfc3986.txt>, January 2005.

73 **[RFC 791]**

74 "Internet Protocol (IPv4)", IETF RFC 791, <http://www.ietf.org/rfc/rfc791.txt>, September 1981.

75 **[RFC 2460]**

76 S. Deering, et al, "Internet Protocol, Version 6 (IPv6) Specification", IETF RFC 2460,
77 <http://www.ietf.org/rfc/rfc2460.txt>, December 1998.

78 **[SOAP 1.1]**

79 W3C Note, "Simple Object Access Protocol (SOAP) 1.1", [http://www.w3.org/TR/2000/NOTE-](http://www.w3.org/TR/2000/NOTE-SOAP-20000508)
80 [SOAP-20000508](http://www.w3.org/TR/2000/NOTE-SOAP-20000508), 08 May 2000.

81 **[SOAP 1.2 Part 1]**

82 W3C Recommendation, "SOAP Version 1.2 Part 1: Messaging Framework (Second Edition)",
83 <http://www.w3.org/TR/2007/REC-soap12-part1-20070427>, April 2007.

84 **[WS-Addressing]**

85 W3C Recommendation, "Web Services Addressing 1.0 - Core", [http://www.w3.org/TR/2006/REC-](http://www.w3.org/TR/2006/REC-ws-addr-core-20060509)
86 [ws-addr-core-20060509](http://www.w3.org/TR/2006/REC-ws-addr-core-20060509), 9 May 2006.

87 **[WS-Security]**

88 OASIS Standard, "Web Services Security Core specification 1.1", [http://www.oasis-](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)
89 [open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf),
90 February 2006.

91 **[XML 1.0]**

92 W3C Recommendation, "Extensible Markup Language (XML) 1.0 (Fourth Edition)",
93 <http://www.w3.org/TR/2006/REC-xml-20060816>, 16 August 2006.

94 2 UDP Packet

95 Except as noted explicitly below, this specification does not constrain RFC 768 [RFC 768]

96

97 2.1 Source Address and Port

98 For security reasons, the source address MUST be supplied at the IP packet level and MUST be the IPv4
99 [RFC 791] address (including but not limited to unicast, multicast, and broadcast addresses) or IPv6 [RFC
100 2460] address (including but not limited to unicast and multicast addresses) of the sender; the receiver
101 SHOULD reject IP packets containing a SOAP/UDP datagram that have inappropriate values for the
102 source address.

103 2.2 Data Octets

104 The data octets MUST contain a SOAP envelope [SOAP 1.1][SOAP 1.2 Part 1]

105 The SOAP envelope MUST fit within a single datagram, that is, it MUST be small enough that the overall
106 datagram is less than 65,536 (2^{16}) octets.

107 The SOAP envelope MUST use the mechanisms defined in WS-Addressing [WS-Addressing]

108

109 3 Message Patterns

110 This specification supports the following message patterns:

- 111 • Unicast one-way
- 112 • Multicast one-way
- 113 • Unicast request, unicast response
- 114 • Multicast request, unicast response

115 as detailed in the rest of this section.

116 This specification uses the constructs **[action]**, **[destination]**, **[message id]**, **[reply endpoint]**,
117 **[address]** in WS-Addressing **[WS-Addressing]**

118 . SOAP messages transmitted over UDP MUST have a **[message id]** property.

119 3.1 One-way

120 The one-way message is sent in a user datagram.

121 3.1.1 One-way Example

```
122 (001) <S:Envelope xmlns:S="http://www.w3.org/2003/05/soap-envelope"  
123     xmlns:wsa="http://www.w3.org/2005/08/addressing" >  
124 (002)   <S:Header>  
125 (003)     <wsa:To>http://fabrikam.com/Server</wsa:To>  
126 (004)     <wsa:Action>http://fabrikam.com/Probe</wsa:Action>  
127 (005)     <wsa:MessageID>  
128         urn:uuid:1da72f1a-5546-493c-934c-a9e3577e206a  
129     </wsa:MessageID>  
130 (006)   </S:Header>  
131 (007)   <S:Body>  
132 (008)     ...  
133 (009)   </S:Body>  
134 (010) </S:Envelope>
```

135 This example shows a one-way SOAP message. Lines 001-002 are standard SOAP elements. Lines 003-
136 005 specify various WS-Addressing headers. Note that despite the fact that the **[destination]** for the
137 message is specified using a URI that uses the http scheme, the message is still transmitted over UDP.
138 Lines 006-010 show standard SOAP elements.

139 3.2 Request-response

140 The request message is sent in one user datagram and the corresponding response message is sent in
141 another user datagram.

142 3.2.1 Anonymous [reply endpoint]

143 WS-Addressing defines a URI, "http://www.w3.org/2005/08/addressing/anonymous", that can appear in
144 the **[address]** property of an endpoint reference. If the **[reply endpoint]** property of a SOAP message
145 transmitted over UDP has an **[address]** property with this value, the UDP source address (and source
146 port) is considered to be the address to which reply messages should be sent.

147 The implied value of the **[reply endpoint]** property for SOAP messages transmitted over UDP is an
148 endpoint reference with an **[address]** property whose value is
149 "http://www.w3.org/2005/08/addressing/anonymous".

150 3.2.2 Request Example 1

```
151 (001) <S:Envelope xmlns:S=http://www.w3.org/2003/05/soap-envelope  
152         xmlns:wsa="http://www.w3.org/2005/08/addressing" >  
153 (002)   <S:Header>  
154 (003)     <wsa:To>http://fabrikam.com/Server</wsa:To>  
155 (004)     <wsa:Action>http://fabrikam.com/Probe</wsa:Action>  
156 (005)     <wsa:MessageID>  
157             urn:uuid:9ceada16-2403-4404-a8cc-60799acd9d1c  
158             </wsa:MessageID>  
159 (006)     <wsa:ReplyTo>  
160             <wsa:Address>  
161                 http://www.w3.org/2005/08/addressing/anonymous  
162             </wsa:Address>  
163             </wsa:ReplyTo>  
164 (007)   </S:Header>  
165 (008)   <S:Body>  
166 (009)     ...  
167 (010)   </S:Body>  
168 (011) </S:Envelope>
```

169 This example shows a request SOAP message. Lines 001-002 are standard SOAP elements. Lines 003-
170 005 specify various WS-Addressing headers. Note that despite the fact that the **[destination]** for the
171 message is specified using a URI that uses the http scheme, the message is still transmitted over UDP.
172 Line 6 shows a **[reply endpoint]** header specifying the anonymous URI (see Section 3.2.1). Lines 007-
173 011 show standard SOAP elements.

174 3.2.3 Response Example 1

```
175 (001) <S:Envelope xmlns:S="http://www.w3.org/2003/05/soap-envelope"  
176         xmlns:wsa="http://www.w3.org/2005/08/addressing" >  
177 (002)   <S:Header>  
178 (003)     <wsa:To>  
179             http://www.w3.org/2005/08/addressing/anonymous  
180             </wsa:To>  
181 (004)     <wsa:Action>http://fabrikam.com/ProbeMatch</wsa:Action>  
182 (005)     <wsa:MessageID>  
183             urn:uuid:5a6ed11a-7a80-409a-82bf-43c4c5092911  
184             </wsa:MessageID>  
185 (006)     <wsa:RelatesTo>  
186             urn:uuid:9ceada16-2403-4404-a8cc-60799acd9d1c  
187             </wsa:RelatesTo>  
188 (007)   </S:Header>  
189 (008)   <S:Body>  
190 (009)     ...  
191 (010)   </S:Body>  
192 (011) </S:Envelope>
```

193 This example shows a response SOAP message. Lines 001-002 are standard SOAP elements. Lines
194 003-005 specify various WS-Addressing headers. Note that the **[destination]** for the message is
195 specified as the anonymous URI. Line 006 shows a **[relationship]** header indicating that this message is
196 a reply to the example message in Section 3.2.2. Lines 007-011 show standard SOAP elements.

197 3.2.4 Request Example 2

```
198 (001) <S:Envelope xmlns:S=http://www.w3.org/2003/05/soap-envelope
199       xmlns:wsa="http://www.w3.org/2005/08/addressing" >
200 (002)   <S:Header>
201 (003)     <wsa:To>soap.udp://fabrikam1.com:54321/Server</wsa:To>
202 (004)     <wsa:Action>http://fabrikam1.com/Probe</wsa:Action>
203 (005)     <wsa:MessageID>
204           urn:uuid:9ceada16-2403-4404-a8cc-60799acd9d1c
205           </wsa:MessageID>
206 (006)     <wsa:ReplyTo>
207           <wsa:Address>
208             soap.udp://fabrikam2.com:54322/Client
209           </wsa:Address>
210           </wsa:ReplyTo>
211 (007)   </S:Header>
212 (008)   <S:Body>
213 (009)     ...
214 (010)   </S:Body>
215 (011) </S:Envelope>
```

216 This example shows a request SOAP message. Lines 001-002 are standard SOAP elements. Lines 003-
217 005 specify various WS-Addressing headers. Note that the **[destination]** for the message is specified
218 using a URI that uses the soap.udp scheme. Line 6 shows a **[reply endpoint]** header containing an
219 addressable URI that uses the soap.udp scheme. Lines 007-011 show standard SOAP elements.

220 3.2.5 Response Example 2

```
221 (001) <S:Envelope xmlns:S="http://www.w3.org/2003/05/soap-envelope"
222       xmlns:wsa="http://www.w3.org/2005/08/addressing" >
223 (002)   <S:Header>
224 (003)     <wsa:To>
225           soap.udp://fabrikam2.com:54322/Client
226           </wsa:To>
227 (004)     <wsa:Action>http://fabrikam.com/ProbeMatch</wsa:Action>
228 (005)     <wsa:MessageID>
229           urn:uuid:5a6ed11a-7a80-409a-82bf-43c4c5092911
230           </wsa:MessageID>
231 (006)     <wsa:RelatesTo>
232           urn:uuid:9ceada16-2403-4404-a8cc-60799acd9d1c
233           </wsa:RelatesTo>
234 (007)   </S:Header>
235 (008)   <S:Body>
236 (009)     ...
237 (010)   </S:Body>
238 (011) </S:Envelope>
```

239 This example shows a response SOAP message. Lines 001-002 are standard SOAP elements. Lines
240 003-005 specify various WS-Addressing headers. Note that the **[destination]** for the message contains
241 an addressable URI that uses the soap.udp scheme. Line 006 shows a **[relationship]** header indicating
242 that this message is a reply to the example message in Section 3.2.4. Lines 007-011 show standard
243 SOAP elements.

244 **3.3 Multicast**

245 The message patterns defined above can be used with unicast or multicast transmission of UDP
246 datagrams with the following restriction: The response in a request-response message pattern **MUST**
247 **NOT** be multicast.

248 Note that in the case of a multicast request, unicast response MEP, the sender of the request might
249 receive multiple responses.

250 Multicast SOAP/UDP datagrams **SHOULD** be scoped to ensure they are not forwarded beyond the
251 boundaries of the administrative system. For IPv4, this can be done with either time-to-live (TTL) field or
252 administrative scopes [**RFC 2365**]

253 depending on what is implemented in the network. For IPv6, this can be done by setting the hop-limit
254 field. If either IPv4 TTL or IPv6 hop-limit is used, it is **RECOMMENDED** that its value be set to 1.

255 The destination IP address of a multicast message **MUST** be a multicast group.

256 **3.4 Retransmission**

257 To avoid repeated packet collisions, any retransmission implementation **SHOULD** observe good practices
258 such as using exponential back-off algorithms and spreading. An implementation **MAY** use the algorithm
259 defined in Appendix A. For each transmission of such a message, the value of the [**message id**] property
260 **MUST** be the same.

261 **4 Message Encoding**

262 The algorithm defined in Appendix F of XML 1.0 [**XML 1.0**] should be used to determine whether a
263 message is encoded as XML. If use of said algorithm does not result in an XML serialization, the
264 encoding is undefined.

265 5 URI Scheme

266 This section defines a URI scheme for UDP endpoints. The scheme allows hostname and port to be
267 specified. Resolving such a URI provides the information needed to send messages to a UDP endpoint
268 per the protocol defined in this document.

269 5.1 Syntax

270 The syntax of the URI scheme is as follows:

```
271 soap.udp://<host>:<port>[/<rel_path>][?<query>]
```

272 The syntax and interpretation of the host, port, rel_path and query portions is as defined in RFC 3986
273 **[RFC 3986]. Error! Reference source not found.**

274 5.2 Semantics

275 The semantics of resolving a soap.udp URI are as follows:

- 276 1. Use the port portion as the port number.
- 277 2. Resolve the host portion to an IP address.
- 278 3. Using the message protocol defined in this document, send a message to the IP address determined
279 in step 2 using the port number determined in step 1.

280 6 Security Considerations

281 It is recommended that all messages be secured using the mechanisms described in **[WS-Security]**
282 to prevent tampering or falsification.

283 All critical headers, such as those described in **[WS-Addressing]**
284 , and the message body, need to be included in signatures to bind all parts of the message together.

285 Recipients should verify that the sender has the right to speak for the specified source or response
286 location (if one is provided).

287 Messages should be accepted and processed only from trusted sources (either directly trusted or
288 indirectly trusted via third parties).

289 The UDP packet size introduces a challenge for secure messages due to its limited size. For this reason
290 it is recommended that security tokens not be passed but referenced using the Key Identifier mechanisms
291 described in **[WS-Security]**

292

293 SOAP messages containing a **[reply endpoint]** property transmitted over UDP MAY be rejected by a
294 recipient due to security concerns such as distributed denial-of-service attacks.

295 **7 Conformance**

296 An implementation is not conformant with this specification if it fails to satisfy one or more of the MUST or
297 REQUIRED level requirements defined herein.

298 **A. Appendix (non-normative) — Example**
299 **retransmission algorithm**

300 Constants referenced within the algorithm are defined in Table 1 (for unicast messages) and Table 2 (for
301 unreliable multicast messages). The value of those constants (as defined in Table 1 and Table 2) is non-
302 normative. Implementations and other specifications may override the value of those constants.

303 **Retry and back-off algorithm.**

- 304 1. Transmit;
305 2. if *_UDP_REPEAT <= 0 go to Step 11;
306 3. else *_UDP_REPEAT--;
307 4. Generate a random number T in [UDP_MIN_DELAY .. UDP_MAX_DELAY];
308 5. Wait T milliseconds;
309 6. Retransmit;
310 7. if *_UDP_REPEAT <= 0 goto Step 11;
311 8. else *_UDP_REPEAT--;
312 9. $T = T * 2$; If $T > \text{UDP_UPPER_DELAY}$ then $T = \text{UDP_UPPER_DELAY}$;
313 10. go to 5;
314 11. Done.

315 **Table 1: Protocol Retry and back-off constants for unicast messages**

Constant / Message	Value
UNICAST_UDP_REPEAT	1
UDP_MIN_DELAY	50
UDP_MAX_DELAY	250
UDP_UPPER_DELAY	500

316 **Table 2: Protocol Retry and back-off constants for unreliable multicast messages**

Constant / Message	Value
MULTICAST_UDP_REPEAT	2
UDP_MIN_DELAY	50
UDP_MAX_DELAY	250
UDP_UPPER_DELAY	500

317

318 **B. Appendix (non-normative) — Example duplicate**
319 **detection mechanisms**

320 A receiver keeps a list of the last n messages received along with their **[message id]** properties **[WS-**
321 **Addressing]**

322 1. . When a new (non-duplicate) message arrives, the oldest message is removed from the list.

323 A receiver tracks all messages received in the last x milliseconds along with their **[message id]** property
324 **[WS-Addressing]**

325 2. . Messages received more than x milliseconds ago are removed from the list.

326 For both approaches any message arriving with a **[message id]** property identical to one of those the
327 receiver has in its list is a duplicate. Messages with unique values for the **[message id]** property are not
328 duplicates.

329 The timestamp specified in the Security header block **[WS-Security]**

330 MAY be used to limit the duration for which **[message id]** properties need to be remembered.

331 C. Acknowledgements

332 The following individuals have participated in the creation of this specification and are gratefully
333 acknowledged:

334 **Participants:**

335 Geoff Bullen, Microsoft Corporation
336 Steve Carter, Novell
337 Dan Conti, Microsoft Corporation
338 Doug Davis, IBM
339 Scott deDeugd, IBM
340 Dan Driscoll, Microsoft Corporation
341 Colleen Evans, Microsoft Corporation
342 Max Feingold, Microsoft Corporation
343 Travis Grigsby, IBM
344 Francois Jammes, Schneider Electric
345 Ram Jeyaraman, Microsoft Corporation
346 Mike Kaiser, IBM
347 Supun Kamburugamuva, WSO2
348 Devon Kemp, Canon Inc.
349 Akira Kishida, Canon Inc.
350 Mark Little, Red Hat
351 Dr. Ingo Lueck, Technische Universitaet Dortmund
352 Jonathan Marsh, WSO2
353 Carl Mattocks
354 Antoine Mensch
355 Jaime Meritt, Progress Software
356 Vipul Modi, Microsoft Corporation
357 Anthony Nadalin, IBM
358 Tadahiro Nakamura, Canon Inc.
359 Masahiro Nishio, Canon Inc.
360 Toby Nixon, Microsoft Corporation
361 Shin Ohtake, Fuji Xerox Co., Ltd.
362 Venkat Reddy, CA
363 Alain Regnier, Ricoh Company, Ltd.
364 Hitoshi Sekine, Ricoh Company, Ltd.
365 Hiroshi Tamura, Ricoh Company, Ltd.
366 Minoru Torii, Canon Inc.
367 Asir S Vedamuthu, Microsoft Corporation
368 David Whitehead, Lexmark International Inc.
369 Don Wright, Lexmark International Inc.
370 Prasad Yendluri, Software AG, Inc.
371 Elmar Zeeb, University of Rostock
372 Gottfried Zimmermann

373 374 **Co-authors of the initial contributions:**

375 This document is based on initial contributions to the OASIS WS-DD Technical Committee by the
376 following co-authors.

377 Harold Combs, Lexmark International Inc.
378 Martin Gudgin (editor), Microsoft Corporation
379 John Justice, Microsoft Corporation
380 Gopal Kakivaya, Microsoft Corporation
381 David Lindsey, Lexmark International Inc.
382 David Orchard, BEA Systems, Inc.

383 Alain Regnier, Ricoh Company Limited
384 Jeffrey Schlimmer, Microsoft Corporation
385 Stacy Simpson, Lexmark International Inc.
386 Hiroshi Tamura, Ricoh Company Limited
387 Don Wright, Lexmark International Inc.
388 Kenny Wolf, Microsoft Corporation
389

390 **Acknowledgements of the initial contributions:**

391 This specification has been developed as a result of joint work with many individuals and teams,
392 including:

393
394 Erik Christensen, Microsoft Corporation
395 David Langworthy, Microsoft Corporation
396 Yaniv Pessach, Microsoft Corporation
397 Stefan Pharies, Microsoft Corporation
398 Sam Rhodus, Lexmark International Inc.
399 Jerry Thrasher, Lexmark International Inc.
400 Mike Vernal, Microsoft Corporation
401 Elliot Waingold, Microsoft Corporation
402 Dave Whitehead, Lexmark International Inc.

403

D. Revision History

404

[optional; should not be included in OASIS Standards]

405

Revision	Date	Editor	Changes Made
wd-01	09/16/2008	Ram Jeyaraman	Created the initial working draft by converting the input specification to OASIS template.
wd-02	09/29/2008	Ram Jeyaraman	Updated document identifier, added co-chair and editor names, use of urn:uuid (issue 50) in examples.
wd-03	1/15/2008	Ram Jeyaraman	Created working draft 03 by applying the proposed resolutions of the following issues to CD-01 version: 116 - Update references and related changes 136 - SOAP-over-UDP - UNICAST_UDP_REPEAT and MULTICAST_UDP_REPEAT constant values Updated copyright year to 2009. Appendix C. Acknowledgements. Included a list of TC participants.

406